

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 November 2005 (03.11.2005)

PCT

(10) International Publication Number  
**WO 2005/103781 A1**

(51) International Patent Classification<sup>7</sup>: **G02B 6/26**

(21) International Application Number:  
PCT/US2005/002853

(22) International Filing Date: 2 February 2005 (02.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PCT/US2004/010048  
31 March 2004 (31.03.2004) US

(71) Applicant (for all designated States except US): **ZOLO TECHNOLOGIES, INC.** [US/US]; 4946 North 63rd Street, Boulder, CO 80301 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MASTERSON, Bernard, Patrick** [US/US]; 325 West Eisenhower Drive, Louisville, CO 80027 (US). **HUELSON, Eric,**

C. [US/US]; 600 Boyd Street, Golden, CO 80403 (US). **SMITH, Ian, S.** [GB/US]; 4715 Tally Ho Court, Boulder, CO 80301 (US).


(74) Agents: **SWANSON, Barry, J.** et al.; Swanson & Bratschun, LLC, 1745 Shea Center Drive, Suite 330, Highlands Ranch, CO 80129 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: OPTICAL MODE NOISE AVERAGING DEVICE



(57) Abstract: An optical mode noise averaging device (300) including a multimode optical fiber (302) and means (308) for averaging a modal noise induced signal level variation of light propagating within the multimode optical fiber (302). The device may average modal noise induced signal level variations by cyclically varying an index of refraction of the multimode optical fiber (302) over a select period of time, scrambling a light distribution within the multimode optical fiber (302), or both. The index of refraction of the multimode optical fiber may be cyclically varied by cyclically varying the temperature of the multimode optical fiber (302). Alternatively, the index for refraction may be varied or the light distribution within the multimode optical fiber may be scrambled by cyclically manipulating the multimode optical fiber (302).

WO 2005/103781 A1



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*